



OAT PG Heat Transfer Fluid Technical Data Sheet

Product Overview

SOLUTHERM™ OAT PG is a ready-to-use, propylene glycol-based thermal management fluid designed for the unique needs of Direct Liquid Cooling (DLC) in data centres, supercomputers, and adjacent end uses. The fluid offers excellent heat transfer and corrosion protection in these applications. **OAT PG** is a robust PG formulation for direct-to-chip cooling systems. PG 25 fluids have been shown to improve facility PUE, increase computing density and decrease data centre footprint when compared with air-cooled systems.

Product Technical Information

SOLUTHERM™ OAT PG leverages a proprietary Organic Acid Technology inhibitor system that offers long-life corrosion protection for copper, brass, steel, cast iron, and aluminum alloys. **OAT PG** offers great performance evident by modified industry standard ASTM D8040 test designed by *Open Compute Project (OCP)* for corrosion protection. **SOLUTHERM™ OAT PG** is compatible* and well suited for systems which use HNBR, NBR, VMQ, FKM, EPDM, PP, rubbers/elastomers. Additional material compatibility information may be available upon request. **OAT PG** uses a propylene glycol-based formula, which is less toxic than traditional ethylene glycol-based HTFs.

Performance Features and Benefits

- For direct liquid cooling computer applications.
- Protects copper, stainless steel, aluminum, brass, and cast iron against corrosion.
- Formulated without 2-EHA, molybdate and BNAS (borate, nitrite, amine, silicate).
- Product can be maintained with easy, periodic health monitoring and treatment as needed.
- Product offers high temperature corrosion protection for aluminum and is compatible with all aluminum heat exchangers.
- Product is designed to be more environmentally friendly through advanced formulation reducing the toxicity of the fluid compared to similar products.

*As noted in the Open Compute Project Whitepaper: *Guidelines to Rack Manifold Requirements and Qualification*
www.opencompute.org/documents/ocp-white-paper-rackmanifold-requirements-and-qualification-v3-pdf



SOLUTHERM™ is a brand of PFX Group, other brands include:



CONTACT US:
CUSTOMERSERVICE@RECOCHEM.COM
1-800-361-6030

Product Use

SOLUTHERM™ OAT PG is intended for use in Direct Liquid Cooling applications where a water or propylene glycol-based coolant is required. Before the initial fill with **OAT PG**, the system should be prepared by an appropriate flushing procedure followed by complete removal of flushing fluid. There is no need for additional bio treatment with proper maintenance of glycol concentration at or above 25%.

Once filled in cooling system, it is natural for **OAT PG** thermal management fluid inhibitor levels to slowly depreciate over time. Can be maintained in the system with proper fluid monitoring and maintenance according to **SOLUTHERM™** guidance and the addition of recommended **SOLUTHERM™** booster packages.

Storage and Disposal

Store **SOLUTHERM™ OAT PG** in the original container in a cool, dry environment away from direct sunlight. Do not use galvanized steel for storage or handling systems. Refer to SDS for product safety information. Discard unused or end of life product in accordance with local, regional, or national regulations.

Specifications

The corrosion inhibitor package in **SOLUTHERM™ OAT PG** Computer Coolant was designed for use with the following OEM and industrial specifications:

- ASTM D6208
- CoolIT 756-00003
- ASTM D8039

PRODUCT OFFERING INCLUDES:

TYPICAL PROPERTIES	SOLUTHERM™ OAT PG 25	SOLUTHERM™ OAT PG Concentrate	SOLUTHERM™ OAT PG Booster Pack
Propylene glycol % weight	25%	86%	Can be customized to prolong the life of fluid in existing systems.
Corrosion inhibitors and water % weight	75%	14%	
Colour	Fluorescent green	Fluorescent green	
ASTM Corrosion specification	D8039†	D8039	
pH of solution	8.3	Depending on dilution	
Pounds per gallon 68°F (20°C)	8.57	8.84	
Boiling point**	214°F (101°C)	Depending on dilution	
Freezing point	15°F (-9°C)	Depending on dilution	

†ASTM D8039 specification states that Heat Transfer Fluids must contain 30% or more glycol content; fluids not meeting the ASTM specified amount are tested as is using ASTM D8040 and ASTM D1881 and held to the same corrosion and foam control protection specifications stated in the standard.

**Per ASTM D1120



Find out more ►
www.solutherm.com



SOLUTHERM™ is a brand of PFX Group, other brands include:



CONTACT US:
CUSTOMERSERVICE@RECOCHEM.COM
1-800-361-6030